



污水处理 家庭供水 城市用水 工业用水



... Life from purity



一、产品概述 / Product Overview

PT立式单级管道循环泵(以下简称电泵),根据企业标准所规定的性能参数,并结合本公司多年生产经验而设计的新一代产品。泵结构紧凑、体积小、外形美观、安装占地面积小、运行稳定、使用寿命长、效率高、耗电省、装修方便等优点。并可根据扬程与流量的需要串联使用。本电泵由电动机,机械密封,水泵三部分组成,电机为单相或三相异步电动机;水泵与电动机间采用机械密封,电泵转子轴采用优质碳钢材料,并进行防腐处理,确保轴有更高可靠的机械强度,可有效地提高轴的耐磨性和耐腐蚀性,同时也有便于叶轮的维修和拆卸,泵各固定止口密封处采用“O”形橡胶密封圈作静密封。

PT Vertical single-stage pipeline pump are the new generation products according to the enterprise standards and with many years of design experience. The pump has the advantages of compact structure. Small volume, beautiful appearance, small install area, stable operation, long service life, high efficiency, low power consumption, convenient installation and maintain etc. The pump is composed of motor, mechanical seal and pump part. With high quality 45# steel shaft, chrome plating processing ensure the strength and corrosion resistance.

技术参数 / Parameter

型号 Type	流量Q (L/S)	扬程 (m)	最大流量 (m³/h)	最大扬程 (m)	功率 (kW)	电压 (V)	同步转速n (r/min)	配管内径 (mm)
25PT4-22-0.75*	4	22	8	26	0.75	380	3000	25
25PT4-22-0.75D*	4	22	8	26	0.75	220	3000	25
25PT4-27-1.1*	4	27	8	32	1.1	380	3000	25
25PT4-27-1.1D*	4	27	8	32	1.1	220	3000	25
32PT6-20-0.75*	6	20	10	26	0.75	380	3000	32
32PT6-20-0.75D*	6	20	10	26	0.75	220	3000	32
32PT6-25-1.1*	6	25	10	32	1.1	380	3000	32
32PT6-25-1.1D*	6	25	10	32	1.1	220	3000	32
40PT8-15-0.75*	8	15	16	18	0.75	380	3000	40
40PT8-15-0.75D*	8	15	16	18	0.75	220	3000	40
40PT8-18-1.1*	8	18	16	22	1.1	380	3000	40
40PT8-18-1.1D*	8	18	16	22	1.1	220	3000	40
50PT10-15/0.75*	10	15	22	18	0.75	380	3000	50
50PT10-15/0.75D*	10	15	22	18	0.75	220	3000	50
50PT10-20/1.1*	10	20	25	22	1.1	380	3000	50
50PT10-20/1.1D*	10	20	25	22	1.1	220	3000	50
50PT12-20/1.5*	12	20	25	24	1.5	380	3000	50
50PT12-20/1.5D*	12	20	25	24	1.5	220	3000	50
50PT12-25/2.2*	12	25	26	30	2.2	380	3000	50
50PT12-25/2.2D*	12	25	26	30	2.2	220	3000	50
50PT15-30/3*	15	30	29	35	3	380	3000	50
50PT25-40/5.5*	25	40	46	46	5.5	380	3000	50
50PT25-48/7.5*	25	48	50	56	7.5	380	3000	50
65PT20-12/1.1	20	12	35	16	1.1	380	3000	65
65PT20-12/1.1D	20	12	35	16	1.1	220	3000	65
65PT20-15/1.5	20	15	36	18	1.5	380	3000	65
65PT20-15/1.5D	20	15	36	18	1.5	220	3000	65
65PT20-20/2.2	20	20	42	24	2.2	380	3000	65
65PT20-20/2.2D	20	20	42	24	2.2	220	3000	65
65PT25-25/3	25	25	48	31	3	380	3000	65
65PT25-25/3D	25	25	48	31	3	220	3000	65
65PT30-28/4	30	28	52	36	4	380	3000	65
65PT35-30/5.5	35	30	66	33	5.5	380	3000	65
65PT40-40/7.5	40	40	70	40	7.5	380	3000	65
80PT50-15/4	50	15	72	20	4	380	3000	80
80PT60-18/5.5	60	18	77	25	5.5	380	3000	80
80PT60-22/7.5	60	22	78	29	4.5	380	3000	80
80PT70-25/9.2	70	25	86	34	9.2	380	3000	80
80PT70-35/15	70	35	86	46	15	380	3000	80
100PT100-25/11	100	25	150	29	11	380	3000	100
100PT100-28/15	100	28	150	32	15	380	3000	100
100PT100-35/18.5	100	35	150	39	18.5	380	3000	100
100PT120-42/22	120	42	155	52	22	380	3000	100
100PT120-50/30	120	55	158	62	30	380	3000	100

注: *表示不锈钢叶轮